



MAIN FEATURES



Complete group made of load cell and electronic weight indicator, designed to weigh suspended loads.

Display indications: weight (5 digit), stable weight, measuring unit and battery life.
Tare zero and weight settings.
Measuring units selection (kg – N – kN – lb).
Automatic power-off selection.
Digital filter selection.
Peak function and Hold function.

| | |
|----------------------------|-------------------|
| Accuracy: | ± 0,1% f.s. |
| Working temperature: | -5 ÷ +55 °C |
| Power supply: | 3 battery type AA |
| Battery life: | 180 h |
| Load cell safe load limit: | 200% f.s. |
| Breaking load coefficient: | > 5 |
| Protection: | IP62 EN 60529 |
| Bag case | PVC |

DIMENSIONS, CAPACITY AND OPTIONS

| Capacity | Division | Dimensions [mm] | | | Weight |
|----------|----------|-----------------|----|----|--------|
| | | A | B | C | |
| kg | kg | | | | kg |
| 50 | 0,02 | 158 | 12 | 16 | 1,3 |
| 100 | 0,05 | 158 | 12 | 16 | 1,3 |
| 300 | 0,1 | 158 | 12 | 16 | 1,3 |
| 600 | 0,2 | 170 | 16 | 21 | 2,3 |
| 1000 | 0,5 | 170 | 16 | 21 | 2,3 |

Infrared remote control for power-on and tare zeroing.

